

# COMMERCIAL CEILING HEATERS

## RECESS - SURFACE - T-BAR MOUNTING



### 3380 SERIES

- Fan purge circuit (requires 4 wire supply when remote wall thermostat is used with the unit)
- Disconnect switch
- Optional factory installed thermostat
- White powder coated 18 ga. steel grill
- Automatic reset thermal limit
- Steel block fin element
- Vane axial fan blade:
  - 1.5kw - 4.0kw units: 700 RPM motor; 175 CFM
  - 4.8kw units: 900 RPM motor; 200 CFM
- Weight 22 lbs.
- Rough in dimensions: 14 3/16" wide x 19 5/16" high x 4" deep
- Grill dimensions - 15 3/8" wide x 20 9/64" high

UPC 686334	MODEL	KW	BTU'S	VOLTS	PH	AMPS	TEMP RISE	LIST
366489	E3383D-RP	1.5	5120	120	1	12.5	27 °F	<b>545</b>
366298	F3386D-RP	4.0	13600	208		19.2	72 °F	<b>573</b>
366304	F3387D-RP	4.8	16382	208		23.1	76 °F	<b>645</b>
366342	HF3384D-RP	2.0 / 1.5	6826/5120	240/208		8.3/7.2	36 °F	<b>501</b>
366359	HF3385D-RP	3.0 / 2.3	10200/7679	240/208		12.5/10.8	54 °F	<b>571</b>
366366	HF3386D-RP	4.0 / 3.0	13600/10200	240/208		16.8/14.4	72 °F	<b>571</b>
366373	H3387D-RP	4.8	16382	240		20.0	76 °F	<b>644</b>
366410	G3384D-RP	2.0	6826	277		7.2	36 °F	<b>571</b>
366427	G3385D-RP	3.0	10200	277		10.8	54 °F	<b>645</b>
366434	G3386D-RP	4.0	13600	277		14.4	72 °F	<b>645</b>
366441	G3387D-RP	4.8	16382	277	17.3	76 °F	<b>715</b>	



### ACCESSORIES:

UPC 686334	MODEL	DESCRIPTION	WT.	LIST
377850	BOX3310	Additional back can	10 lbs	<b>89</b>
381109	3380EX33R	Surface Mounting Adaptor	1 lb	<b>79</b>
460026	TB3380A	2X2 T-Bar Mounting Kit	7 lbs	<b>53</b>
T-suffix		Factory installed single pole thermostat 50 - 90°F		<b>103</b>

# FAN FORCED CEILING HEATERS

## WITH SELECTABLE WATTAGES, BACK CANS AND POWER DISCONNECT



- Wattage selectable at time of installation - models shipped wired to highest wattage
- Fan purge circuit (requires 4 wire supply when remote single pole wall thermostat is used with the unit)
- Models may not be used with remote double pole thermostat
- Drywall depth embossments on back can
- Powder coated 18 ga. steel front
- Manual reset thermal limit
- Steel block fin element
- Propeller style fan blade - 1060 RPM / 100 CFM
- Weight 6 lbs.
- Optional field installed control voltage relays available
- Rough in dimensions - 9 1/4" wide - 12 1/8" high - 3 5/8" deep
- Grill dimensions: 9 25/32" wide - 13" high

### FIELD INSTALLED ACCESSORIES

UPC 686334	MODEL	DESCRIPTION	LIST
996846	30R	24 VOLT RELAY	<b>32</b>
996853	30R2	120 VOLT RELAY	<b>32</b>
951500	30R8	208/240 VOLT RELAY	<b>34</b>
951494	30R7	277 VOLT RELAY	<b>34</b>

UPC 686334	MODEL	DESCRIPTION	LIST
996976	303EX8RW	1" EXTENDER	<b>34</b>
996969	303EX16RW	2" EXTENDER	<b>35</b>
996952	303EX32RW	4" SURFACE MOUNT FRAME	<b>40</b>
460033	TB3000	T-BAR FRAME	<b>53</b>

WHITE		SELECTABLE INSTALLATION WATTAGE	MAX BTU'S	VOLTS	MAX AMPS	LIST
UPC 686334	MODEL					
948821	E3035DWBW	750 or 1500	5120	120	12.5	<b>235</b>
948838	E3038DWBW	900 or 1800	6143	120	15.0	<b>235</b>
948883	H3032DWBW	750 or 1000 - 1500 or 2000	6826	208 / 240	8.3	<b>235</b>
948906	G3032DWBW	2000	6826	277	7.2	<b>235</b>