

3000 Series Midsized Commercial Fan Forced Wall Heater - Multiple Wattage

77



Approved for
wall or ceiling
installation

Features

- Wattage selectable at time of installation.
- Models shipped wired to highest wattage.
- Approved for horizontal mounting - right or left discharge.
- Fan purge circuit.
- Disconnect switch.
- Drywall depth embossments on back can.
- 18 Gauge powder coated steel & extruded aluminum front.
- Manual reset thermal limit.
- Steel block fin element.
- Propeller style fan blade: 1060 RPM motor; 100 CFM.
- Weight 6 lbs.
- Rough in dimensions: 9 1/4" wide x 12 1/8" high x 3 5/8" deep.
- Grill dimensions: 10" wide x 13 1/8" high.

Standard Models

UPC 686334	MODEL	SELECTABLE INSTALATION WATTAGE	MAX BTU's	VOLTS	MAX AMPS
TAMPERPROOF IN-BUILT DOUBLE POLE THERMOSTAT (50° - 90° TEMPERATURE RANGE)					
996211	E3055T2DWB	750 or 1500	5120	120	12.5
996228	E3058T2DWB	900 or 1800	6143	120	15.0
996259	F3052T2DWB	1000 or 2000	6826	208	8.3
945691	F30522T2DWB	500 or 750 or 1000 or 1250 or 1500 or 1750 or 2250	7680	208	10.8
996280	H3052T2DWB	750 or 1000 - 1500 or 2000	6826	208 / 240	8.3
945721	H30522T2DWB	500 or 750 or 1000 or 1250 or 1500 or 1750 or 2250	7680	240	9.4
996310	G3052T2DWB	2000	6826	277	7.2
TAMPERPROOF IN-BUILT DOUBLE POLE THERMOSTAT (50° - 90° TEMPERATURE RANGE)					
996068	E3055TDWB	750 or 1500	5120	120	12.5
996075	E3058TDWB	900 or 1800	6143	120	15.0
996105	F3052TDWB	1000 or 2000	6826	208	8.3
945639	F30522TDWB	500 or 750 or 1000 or 1250 or 1500 or 1750 or 2250	7680	208	10.8
996136	H3052TDWB	750 or 1000 - 1500 or 2000	6826	208 / 240	8.3
945660	H30522TDWB	500 or 750 or 1000 or 1250 or 1500 or 1750 or 2250	7680	240	9.4
996167	G3052TDWB	2000	6826	277	7.2

Accessories

UPC 686334	MODEL	DESCRIPTION
996945	305EX8	1" EXTENDER
996938	305EX16	2" EXTENDER
996921	305EX32	4" SURFACE MOUNT FRAME

AFA Series Commercial Fan Forced Wall Heater

78



Features

- Disconnect switch.
- Automatic fan delay circuit.
- Powder coated 18 Gauge steel grill with extruded aluminum front frame.
- Automatic reset thermal limit.
- Steel block fin element.
- Vane axial fan blade:
600 RPM motor; 175 CFM
- Rough-in dimensions:
14-3/16" wide x 19-15/16" high x 4" deep
- Grill dimensions:
15-29/32" wide x 20-27/32" high



Product Specifications

Furnish and install Heavy-Duty Forced Air wall heaters, where specified. The heaters shall be constructed of a heavy 18 Gauge steel housing with an extruded aluminum frame. The rough-in dimensions are 19-5/16" high x 14-3/16" wide x 4" deep. The units shall be available in ratings from 750 to 4800 Watts at 240, 208, and 277 Volts. The heaters shall have a low-speed 600 RPM, 4-pole motor which drives a vane axial blower to deliver a quiet 175 CFM of down flow air. The heating element shall be of the sealed tubular type with large, parallel steel fins for quick heat transfer. Unit shall have as a standard, a thermal overload cut-off for added safety, fan delay switch and built-in tamperproof thermostat which shall be calibrated to provide a range of 55°F. to 85°F. and manual disconnect switch.

Optional accessories shall include a surface and semi-recess mounting adapter. All heaters shall be listed by Underwriter's Laboratories, Inc. The heating element shall be supplied with a manufactures 1-year limited warranty.

Standard Models

UPC#	MODEL	WATTS	BTU's	VOLTS	AMPS	WT. Lbs.
686334						
IN-BUILT SINGLE POLE TAMPERPROOF THERMOSTAT (50° - 90° TEMPERATURE RANGE) FOR DOUBLE POLE THERMOSTAT REPLACE "TT" IN MODEL NUMBER WITH "T2"						
328593	AFA107D	750	2560	120	6.25	26
328609	AFA110D	1000	3413		8.3	
328616	AFA115D	1500	5120		12.5	
328623	AFA840D	4000	13800	208	19.2	29
328630	AFA848D	4800	16560		23	
328647	AFA215D	1500/1125	5120 / 3840	240 / 208	6.2 / 5.4	27
328654	AFA220D	2000 / 1500	6284 / 5120		8.3 / 7.2	
328661	AFA230D	3000 / 2250	10350 / 7763		12.5 / 10.8	
328678	AFA240D	4000 / 3000	13800 / 10350	240	16.7/14.4	29
328685	AFA248D	4800	16560		20	
328692	AFA715D	1500	5120		4.1	
328708	AFA720D	2000	6284	277	7.2	27
328715	AFA730D	3000	10350		10.8	
328722	AFA740D	4000	13800		14.4	
328739	AFA748D	4800	16560		17.3	

Accessories

UPC#	MODEL	DESCRIPTION	TYPE	WT. lbs.
686334				
328746	BOX AFA	Additional Rough-in Box	Field Installed	3
328753	AFAEX33	4" Surface Mounting Frame		1
328760	AFAEX16	2" semi recess extender		1
-----	Suffix - HD	16 Gauge Steel Heavy Duty Grill	Factory Installed	2

4400 Series Low Profile Commercial Fan Forced Wall Heater - With Wall Box



- Powder coated 20 Gauge steel front with extruded aluminum frame.
- Manual reset thermal limit.
- Finned tubular steel element.
- Propeller style fan blade - 2200 RPM/70 CFM
- Weight 9 lbs.
- Rough in dimensions:
14 1/2" wide x 7 1/8" high x 3 1/2" deep
- Grill dimensions: 16 7/8" wide x 8" high
- Unit not approved for ceiling mount applications.
- Unit can be positioned to allow left, right or top discharge.

Standard Models

UPC 686334	MODEL	VOLTS	WATTS	MAX BTU'S	AMPS
DOUBLE POLE IN-BUILT THERMOSTAT (RANGE 50° - 90° F)					
328326	F4420T2RP	208	2000	6826	9.6
328333	HF4475T2RP	240/208	750 / 562	2560 / 1920	3.1 / 2.7
328340	HF4410T2RP		1000 / 750	3413 / 2560	4.2 / 3.6
328357	HF4415T2RP		1500 / 1125	5120 / 3840	6.3 / 5.4
328364	HF4420T2RP		2000 / 1500	6826 / 5120	8.3 / 7.2
SINGLE POLE IN-BUILT THERMOSTAT (RANGE 50° - 90° F)					
328371	E4475TRP	120	750	2560	6.25
328388	E4410TRP		1000	3413	8.33
328395	E4415TRP		1500	5120	12.5
328401	F4420TRP	208	2000	6826	9.6

Accessories

UPC	MODEL	DESCRIPTION	WT. LBS.
686334			
329910	4400EX8	1" SEMI RECESSING EXTENDER	2
329903	4400EX16	2" SEMI RECESSING EXTENDER	3
329897	4400EX32	4" SURFACE MOUNTING FRAME	4
328449	4300PB	WALL PLATE ADAPTOR (OD 21.5"x12.25")	1