

COMMERCIAL CEILING HEATERS

RECESS - SURFACE - T-BAR MOUNTING



3380 SERIES

- Fan purge circuit (requires 4 wire supply when remote wall thermostat is used with the unit)
- Disconnect switch
- Optional factory installed thermostat
- White powder coated 18 ga. steel grill
- Automatic reset thermal limit
- Steel block fin element
- Vane axial fan blade:
 - 1.5kw - 4.0kw units: 700 RPM motor; 175 CFM
 - 4.8kw units: 900 RPM motor; 200 CFM
- Weight 22 lbs.
- Rough in dimensions: 14 3/16" wide x 19 5/16" high x 4" deep
- Grill dimensions - 15 3/8" wide x 20 9/64" high

See page 69 for single pole line voltage wall thermostats

UPC 686334	MODEL	KW	BTU'S	VOLTS	PH	AMPS	TEMP RISE	LIST
366489	E3383D-RP	1.5	5120	120	1	12.5	27 °F	545
366298	F3386D-RP	4.0	13600	208		19.2	72 °F	573
366304	F3387D-RP	4.8	16382	208		23.1	76 °F	645
366342	HF3384D-RP	2.0 / 1.5	6826/5120	240/208		8.3/7.2	36 °F	501
366359	HF3385D-RP	3.0 / 2.3	10200/7679	240/208		12.5/10.8	54 °F	571
366366	HF3386D-RP	4.0 / 3.0	13600/10200	240/208		16.8/14.4	72 °F	571
366373	H3387D-RP	4.8	16382	240		20.0	76 °F	644
366410	G3384D-RP	2.0	6826	277		7.2	36 °F	571
366427	G3385D-RP	3.0	10200	277		10.8	54 °F	645
366434	G3386D-RP	4.0	13600	277		14.4	72 °F	645
366441	G3387D-RP	4.8	16382	277		17.3	76 °F	715



ACCESSORIES:

UPC 686334	MODEL	DESCRIPTION	WT.	LIST
377850	BOX3310	Additional back can	10 lbs	89
381109	3380EX33R	Surface Mounting Adaptor	1 lb	79
460026	TB3380A	2X2 T-Bar Mounting Kit	7 lbs	53
T-suffix		Factory installed single pole thermostat 50 - 90°F		103

FAN FORCED CEILING HEATERS

WITH SELECTABLE WATTAGES, BACK CANS AND POWER DISCONNECT



- Wattage selectable at time of installation - models shipped wired to highest wattage
- Fan purge circuit (requires 4 wire supply when remote single pole wall thermostat is used with the unit)
- Models may not be used with remote double pole thermostat
- Drywall depth embossments on back can
- Powder coated 18 ga. steel front
- Manual reset thermal limit
- Steel block fin element
- Propeller style fan blade - 1060 RPM / 100 CFM
- Weight 6 lbs.
- Optional field installed control voltage relays available
- Rough in dimensions - 9 1/4" wide - 12 1/8" high - 3 5/8" deep
- Grill dimensions: 9 25/32" wide - 13" high

FIELD INSTALLED ACCESSORIES

UPC 686334	MODEL	DESCRIPTION	LIST
996846	30R	24 VOLT RELAY	32
996853	30R2	120 VOLT RELAY	32
951500	30R8	208/240 VOLT RELAY	34
951494	30R7	277 VOLT RELAY	34

UPC 686334	MODEL	DESCRIPTION	LIST
996976	303EX8RW	1" EXTENDER	34
996969	303EX16RW	2" EXTENDER	35
996952	303EX32RW	4" SURFACE MOUNT FRAME	40
460033	TB3000	T-BAR FRAME	53

WHITE		SELECTABLE INSTALLATION WATTAGE	MAX BTU'S	VOLTS	MAX AMPS	LIST
UPC 686334	MODEL					
948821	E3035DWBW	750 or 1500	5120	120	12.5	235
948838	E3038DWBW	900 or 1800	6143	120	15.0	235
948883	H3032DWBW	750 or 1000 - 1500 or 2000	6826	208 / 240	8.3	235
948906	G3032DWBW	2000	6826	277	7.2	235