

COMMERCIAL FAN FORCED WALL HEATERS



AFA SERIES

- Disconnect switch
- Automatic fan delay circuit
- Powder coated 18ga. steel grill with extruded aluminum front frame
- Automatic reset thermal limit

- Steel block fin element
- Vane axial fan blade: 600 RPM motor ; 175 CFM
- Rough-in dimensions - 14 3/16" wide x 19 15/16" high x 4" deep
- Grill dimensions - 15 29/32" wide x 20 27/32" high



**MODELS WITH
IN-BUILT
SINGLE POLE
TAMPERPROOF
THERMOSTAT**
(50°-90°F temp range)

UPC 686334	MODEL	WATTS	BTU's	VOLTS	AMPS	WT. Lbs.	LIST
328593	AFA107D	750	2560	120	6.25	26	589
328609	AFA110D	1000	3413		8.3		589
328616	AFA115D	1500	5120		12.5		590
328623	AFA840D	4000	13800	208	19.2	26	600
328630	AFA848D	4800	16560		23		630
328647	AFA215D	1500 / 1125	5120 / 3840	240 / 208	6.2 / 5.4	27	600
328654	AFA220D	2000 / 1500	6284 / 5120		8.3 / 7.2		600
328661	AFA230D	3000 / 2250	10350 / 7763		12.5 / 10.8	29	600
328678	AFA240D	4000 / 3000	13800 / 10350	277	16.7 / 14.4		600
328685	AFA248D	4800	16560		20		624
328692	AFA715D	1500	5120		4.1	26	599
328708	AFA720D	2000	6284		7.2	27	599
328715	AFA730D	3000	10350		10.8	29	599
328722	AFA740D	4000	13800		14.4		599
328739	AFA748D	4800	16560		17.3		617

FOR MODELS WITH IN-BUILT DOUBLE
POLE TAMPERPROOF THERMOSTAT
CHANGE T IN MODEL NUMBER TO T2
AND ADD \$50 TO LIST

UPC 686334	MODEL	DESCRIPTION	TYPE	WT. lbs.	LIST
328746	BOX AFA	Additional Rough-in Box	Field Installed	3	91
328753	AFAEX33	4" Surface Mounting Frame		1	81
328760	AFAEX16	2" semi recess extender		1	69
-----	Suffix - HD	16 Ga. Steel Heavy Duty Grill	Factory Installed	2	91

LOW PROFILE COMMERCIAL FAN FORCED WALL HEATERS (WITH WALL BOX)



- Powder coated 20 ga. steel front with extruded aluminum frame
- Manual reset thermal limit
- Finned tubular steel element
- Propeller style fan blade - 2200 RPM / 70 CFM
- Weight 9 lbs.
- Rough in dimensions - 14 1/2" wide - 7 1/8" high - 3 1/2" deep
- Grill dimensions - 16 7/8" wide - 8" high
- Unit not approved for ceiling mount applications
- Unit can be positioned to allow left, right or top discharge



**DOUBLE POLE
IN-BUILT
THERMOSTAT**
(range 50°-90°F)

UPC 686334	MODEL	VOLTS	WATTS	MAX BTU'S	AMPS	LIST
328326	F4420T2RP	208	2000	6826	9.6	291
328333	HF4475T2RP	240/208	750 / 562	2560 / 1920	3.1 / 2.7	
328340	HF4410T2RP		1000 / 750	3413 / 2560	4.2 / 3.6	
328357	HF4415T2RP		1500 / 1125	5120 / 3840	6.3 / 5.4	
328364	HF4420T2RP		2000 / 1500	6826 / 5120	8.3 / 7.2	

**SINGLE POLE
IN-BUILT
THERMOSTAT**
(range 50°-90°F)

328371	E4475TRP	120	750	2560	6.25	274
328388	E4410TRP		1000	3413	8.33	
328395	E4415TRP		1500	5120	12.5	
328401	F4420TRP	208	2000	6826	9.6	

ACCESSORIES

UPC 686334	MODEL	ACCESSORY OPTIONS	WT. LBS.	LIST
329910	4400EX8	1" SEMI RECESSING EXTENDER	2	40
329903	4400EX16	2" SEMI RECESSING EXTENDER	3	43
329897	4400EX32	4" SURFACE MOUNTING FRAME	4	45
328449	4300PB	WALL PLATE ADAPTOR (OD 21.5"x12.25")	1	29