

fostoria[®] HEAT WAVE™ PORTABLE ELECTRIC SALAMANDER

THE ODORLESS, FLAMELESS ELECTRIC ALTERNATIVE TO PROPANE AND KEROSENE SPACE HEATERS



- Safety yellow heater enclosure with safety screens on both air intake and output openings
- Optional 25' long SO type cord, ready for plug attachment is available for each model
- Long-life finned tubular heating elements
- Thermostat adjustment 40° to 100° F
- High-limit thermal cutout switch
- CFM Ratings:
800 CFM - 10/15kW Units
1100 CFM - 30kW units
- Magnetic contactor
- Fan only operation feature

AVERAGE MINUTES TO ACHIEVE TEMPERATURE RISE*						
BUILDING SIZE:	1000 SQ. FEET		1500 SQ. FEET		2000 SQ. FEET	
HEATER:	TEMP RISE		TEMP RISE		TEMP RISE	
	20 °F	40 °F	20 °F	40 °F	20 °F	40 °F
10 KW	70 min	140 min	105 min	210 min	---	---
15 KW	47 min	94 min	71 min	142 min	94 min	188 min
30 KW	23 min	46 min	35 min	70 min	47 min	94 min
45 KW	16 min	31 min	24 min	47 min	32 min	64 min

* Based on a 15' ceiling height - lower ceiling height will reduce time required

UPC 686334	MODEL	KW	BTU's	VOLTS	PH	AMPS	TEMP RISE	WT.	LIST
886017	FES-1520-3A	15	51195	208	3	42	45°F	65 lbs.	1418
886079	FES-1524-1A	15	51195	240	1	63	45°F	69 lbs.	1418
886024	FES-1524-3E	15	51195	240	3	36	45°F	65 lbs.	1418
886031	FES-1548-3E	15	51195	480	3	18	45°F	65 lbs.	1418
886055	FES-3048-3A	30	102390	480	3	36	90°F	83 lbs.	2237

OPTIONAL 25' POWER CORD		
UPC 686334	TYPE	LIST
316408	6/4 SO	273
880534	4/3 SO	352
316408	6/4 SO	273
316422	12/4 SO	130
316408	6/4 SO	273

10KW - 240V - 1 PHASE FACTORY PRE-WIRED MODEL WITH 10 ft. CABLE & STRAIGHT BLADE RANGE PLUG FOR USE WITH A STANDARD RANGE OUTLET.



UPC 686334	MODEL	KW	BTU's	VOLTS	PHASE	AMPS	TEMP RISE	WT.	LIST
886000	FES-1024-1CA	10	34130	240	1	42	30°F	60 lbs.	1418

45KW HEAT WAVE™ PORTABLE ELECTRIC SALAMANDER



- Safety yellow heater enclosure with safety screens on both air intake and output openings
- Optional 25' long SO type cord, ready for plug attachment is available for each model
- Long-life finned tubular heating elements
- Thermostat adjustment 40° to 100° F
- Two 10" rear wheels and a front locking caster
- High-limit thermal cutout switch with manual reset
- 2200 CFM
- Magnetic contactor
- Fan only operation feature



UPC 686334	MODEL	KW	BTU's	VOLTS	PH	AMPS	TEMP RISE	WT.	LIST
872225	FES-4548-3	45	153585	480	3	54.2	70°F	125 lbs.	3700

OPTIONAL 25' POWER CORD		
UPC 686334	TYPE	LIST
316439	4/4 SO	300

WALL / CEILING MOUNT ELECTRIC SALAMANDER

- All YES-Series units can be mounted to either a Wall or Ceiling Surface
- Yoke and Bracket included with each YES Unit
- All units are designed for direct wire installation

CEILING
MOUNT



WALL
MOUNT



UPC 686334	MODEL	KW	BTU's	VOLTS	PHASE	AMPS	TEMP RISE	WT.	LIST
886086	YES-1520-3A	15	51195	208	3	42	45°F	60 lbs.	1418
886185	YES-1524-1A	15	51195	240	1	63	45°F	60 lbs.	1418
886093	YES-1524-3E	15	51195	240	3	36	45°F	60 lbs.	1418
886109	YES-1548-3E	15	51195	480	3	18	45°F	60 lbs.	1418
886123	YES-3048-3A	30	102390	480	3	36	90°F	72 lbs.	2237